



SUSPENSION SETUP CHART

| QUAKE | | | |
|--------------------------------|-----|-------------------------|--|
| MODEL | | QUAKE | |
| SHOCK SPEC | | RS VIVID COIL ULT DH | |
| RIDER WEIGHT | | | |
| LBS | KG | LB/IN (COIL) | |
| 120 | 54 | 300 | |
| 130 | 59 | | |
| 140 | 64 | 350 | |
| 150 | 68 | | |
| 160 | 73 | 400 | |
| 170 | 77 | | |
| 180 | 82 | 450 | |
| 190 | 86 | | |
| 200 | 91 | 500 | |
| 210 | 95 | | |
| 220 | 100 | 550 | |
| 230 | 104 | | |
| 240 | 109 | 600 | |
| 250 | 113 | | |
| 260 | 118 | 650 | |
| 270 | 122 | | |
| RECOMMENED SAG 30% / 22.5MM | | | |

| ALPINE TRAIL | | | |
|--------------------------------|-----|-------------------|------------------------|
| MODEL | | ALPINE TRAIL 1 | ALPINE TRAIL 2 & XR |
| SHOCK SPEC | | X FUSION H3A | RS VIVID AIR |
| RIDER WEIGHT | | | |
| LBS | KG | PSI | PSI |
| 120 | 54 | 130 | 146 |
| 130 | 59 | 140 | 156 |
| 140 | 64 | 150 | 166 |
| 150 | 68 | 160 | 176 |
| 160 | 73 | 170 | 186 |
| 170 | 77 | 181 | 196 |
| 180 | 82 | 192 | 206 |
| 190 | 86 | 203 | 216 |
| 200 | 91 | 214 | 226 |
| 210 | 95 | 226 | 236 |
| 220 | 100 | 237 | 246 |
| 230 | 104 | 245 | 256 |
| 240 | 109 | 257 | 276 |
| 250 | 113 | 269 | 286 |
| 260 | 118 | 282 | 296 |
| 270 | 122 | 295 | 306 |
| RECOMMENED SAG 30% / 19.5MM | | | |

| RIFT ZONE E LIGHT | | | |
|--------------------------------|-----|--|-------------------|
| MODEL | | RIFT ZONE EL XR/2 | RIFT ZONE EL 1 |
| SHOCK SPEC | | FOX FLOAT X PERF - 2 PERF ELITE - XR | MARZ. AIR R |
| RIDER WEIGHT | | | |
| LBS | KG | PSI | PSI |
| 120 | 54 | 130 | 124 |
| 130 | 59 | 145 | 141 |
| 140 | 64 | 155 | 159 |
| 150 | 68 | 170 | 176 |
| 160 | 73 | 185 | 193 |
| 170 | 77 | 200 | 210 |
| 180 | 82 | 215 | 225 |
| 190 | 86 | 230 | 240 |
| 200 | 91 | 245 | 255 |
| 210 | 95 | 260 | 270 |
| 220 | 100 | 275 | 280 |
| 230 | 104 | 290 | 289 |
| 240 | 109 | 300 | 297 |
| 250 | 113 | 310 | 303 |
| 260 | 118 | 315 | 309 |
| 270 | 122 | 319 | 314 |
| RECOMMENED SAG 30% / 16.5MM | | | |



SUSPENSION SETUP CHART

RIFT ZONE

| MODEL | | RIFT ZONE XR | RIFT ZONE 2 (29 & 27.5) | RIFT ZONE 1 (29 & 27.5") |
|--------------|-----|---------------------------------|-------------------------|--------------------------|
| SHOCK SPEC | | ROCK SHOX SUPER DELUXE SELECT + | MARZ. | XF 02 PRO R |
| RIDER WEIGHT | | | | |
| LBS | KG | PSI | PSI | PSI |
| 120 | 54 | 113 | 125 | 118 |
| 130 | 59 | 121 | 135 | 128 |
| 140 | 64 | 130 | 145 | 138 |
| 150 | 68 | 140 | 155 | 150 |
| 160 | 73 | 151 | 165 | 163 |
| 170 | 77 | 163 | 175 | 175 |
| 180 | 82 | 176 | 185 | 188 |
| 190 | 86 | 189 | 196 | 200 |
| 200 | 91 | 202 | 207 | 213 |
| 210 | 95 | 216 | 218 | 225 |
| 220 | 100 | 230 | 230 | 238 |
| 230 | 104 | 244 | 242 | 251 |
| 240 | 109 | 258 | 255 | 265 |
| 250 | 113 | 273 | 268 | 279 |
| 260 | 118 | 288 | 282 | 294 |
| 270 | 122 | 303 | 296 | |

RECOMMENED SAG
30% / 19.5MM

TAM

| MODEL | | TAM 1 | TAM 2 & XR |
|--------------|-----|----------------|--------------|
| SHOCK SPEC | | X FUSION REZZA | FOX FLOAT SL |
| RIDER WEIGHT | | | |
| LBS | KG | PSI | PSI |
| 120 | 54 | 142 | 152 |
| 130 | 59 | 155 | 163 |
| 140 | 64 | 168 | 179 |
| 150 | 68 | 181 | 184 |
| 160 | 73 | 194 | 199 |
| 170 | 77 | 208 | 214 |
| 180 | 82 | 223 | 230 |
| 190 | 86 | 239 | 246 |
| 200 | 91 | 255 | 262 |
| 210 | 95 | 271 | 278 |
| 220 | 100 | 287 | 294 |
| 230 | 104 | 303 | 311 |
| 240 | 109 | 319 | 328 |
| 250 | 113 | 335 | 345 |
| 260 | 118 | 350 | 350 |
| 270 | 122 | | |

RECOMMENED SAG
25% / 11MM

RIFT Z JR.

| MODEL | | RIFT ZONE JR/26" |
|--------------|----|------------------|
| SHOCK SPEC | | XF 02 PRO R |
| RIDER WEIGHT | | |
| LBS | KG | PSI |
| 40 | 18 | 40 |
| 50 | 23 | 50 |
| 60 | 27 | 60 |
| 70 | 32 | 70 |
| 80 | 36 | 80 |
| 90 | 41 | 90 |
| 110 | 50 | 100 |
| 120 | 54 | 110 |

RECOMMENED SAG
30% / 16.5MM